



National Aeronautics and  
Space Administration

**John C. Stennis Space Center**  
Stennis Space Center, MS 39529-6000

**SSTD-8070-0015-WELD**  
**Rev. C**  
**JANUARY 2021**

# **COMPLIANCE IS MANDATORY**

## **John C. Stennis Space Center GAS TUNGSTEN ARC WELD (GTAW) PROCEDURE FOR CARBON STEEL (ASME P-No. 1, GROUP 1 OR 2)**

### **Approved in DDMS by:**

<u>Brennan Sanders</u>	<u>1-8-2021</u>
NASA SSC Center Operations	Date
Facilities Engineering	
Test Complex Support	

<u>Todd Mannion</u>	<u>1-4-2021</u>
NASA SSC Center Operations Directorate	Date
Facilities Services	

<u>Bartt Hebert</u>	<u>1-7-2021</u>
NASA SSC Engineering & Test Directorate	Date

<u>Son Le</u>	<u>1-5-2021</u>
NASA SSC Safety & Mission Assurance	Date

### **Issued by**

<u>ISSUED CEF</u>	<u>1-8-2021</u>
Central Engineering Files	Date

Stennis Standard	SSTD-8070-0015-WELD	C
	<i>Number</i>	<i>Rev.</i>
	Effective Date:	January 11, 2021
	Review Date:	January 11, 2026
Page 2 of 11		
Responsible Office: NASA SSC Center Operations Facilities Engineering Test Complex Support		
<b>SUBJECT: GTAW Procedure for Carbon Steel (ASME P-No. 1, Group 1 or 2)</b>		

## Document History Log

Revision	Date	Originator/ Phone	Description
Basic	04.03.2012	Doug Dike Ext. 8-2803	Initial release. Supersedes SSC-34-008.
A	10.22.2015	Doug Dike Ext. 8-2803	References and acronyms updated. Revised cover sheet to reflect approval by NASA SSC Center Operations Design & Construction Project Management Division; and concurrence by NASA SSC Center Operations Directorate Operations and Maintenance Division, NASA SSC Engineering & Test Directorate, and NASA SSC Safety & Mission Assurance. WPS/PQR attachments clarified.
A-1	08.15.2017	George Smith 8-7680	Administrative changes to attachments to change contractor from FOSC to SACOM.
B	04.20.2020	Benny McGrath Ext. 8-2969	Five-year revision. Updated directorate titles on cover sheet as necessary. Updated references and acronyms. Minor administrative changes. 5.0-b: Added, "and in accordance with ASME Boiler and Pressure Vessel Codes, Section IX, requirements." 5.0-c: Revised to reflect deletion of attached Welder Performance Qualification. 8.4 and 8.5: Deleted Welder Performance Qualifications. Updated WPS to SSC-937.
B-1	05.12.2020	Carol Wolfram 8-1620	Administrative Change. Header effective/review dates updated.
C	01.11.2021	Benny McGrath Ext. 8-2969	WPS updated: Non-essential variable, Position of Groove, changed from "1G" to "ALL".

Stennis Standard	SSTD-8070-0015-WELD	C
	<i>Number</i>	<i>Rev.</i>
	Effective Date:	January 11, 2021
	Review Date:	January 11, 2026
Page 3 of 11		
Responsible Office: NASA SSC Center Operations Facilities Engineering Test Complex Support		
<b>SUBJECT: GTAW Procedure for Carbon Steel (ASME P-No. 1, Group 1 or 2)</b>		

## Table of Contents

<b>1.0</b>	<b>PURPOSE .....</b>	<b>4</b>
<b>2.0</b>	<b>APPLICABILITY .....</b>	<b>4</b>
<b>3.0</b>	<b>REFERENCED AND APPLICABLE DOCUMENTS .....</b>	<b>4</b>
<b>4.0</b>	<b>RESPONSIBILITIES .....</b>	<b>4</b>
<b>5.0</b>	<b>REQUIREMENTS AND PROCEDURES .....</b>	<b>4</b>
<b>6.0</b>	<b>RECORDS AND FORMS .....</b>	<b>5</b>
<b>7.0</b>	<b>ACRONYMS &amp; ABBREVIATIONS .....</b>	<b>5</b>
<b>8.0</b>	<b>ATTACHMENTS .....</b>	<b>6</b>
8.1	Welding Procedure Specification .....	6
8.2	Welding Procedure Qualification Record .....	9
8.3	Certificate of Analysis .....	11

Stennis Standard	SSTD-8070-0015-WELD	C
	<i>Number</i>	<i>Rev.</i>
	Effective Date:	January 11, 2021
	Review Date:	January 11, 2026
Page 4 of 11		
Responsible Office: NASA SSC Center Operations Facilities Engineering Test Complex Support		
<b>SUBJECT: GTAW Procedure for Carbon Steel (ASME P-No. 1, Group 1 or 2)</b>		

## 1.0 PURPOSE

This John C. Stennis Space Center (SSC) standard (SSTD) provides for a qualified American Society of Mechanical Engineers (ASME) weld procedure of Gas Tungsten Arc Welding (GTAW) of carbon steel pipe or plate for 0.1875" to 1.50" wall thickness using argon as a backing gas.

## 2.0 APPLICABILITY

This SSTD is valid for welding of all carbon steel pipe or plate that will be used in, but not limited to, nitrogen, helium, air, and hydrogen service. This SSTD applies to all contractor and subcontractor personnel involved with the welding of carbon steel pipe.

## 3.0 REFERENCED AND APPLICABLE DOCUMENTS

Applicable documents shall be the latest version unless otherwise specified.

ASME Boiler and Pressure Vessel Codes, Section IX, *Welding, Brazing, and Fusing Qualifications*

SPR 1440.1, *SSC Records Management Program Requirements*

SPR 8715.1, *SSC Safety and Health Program Requirements*

SSTD-8070-0005-CONFIG, *Preparation, Review, Approval and Release of SSC Standards*

SSTD-8070-0013-WELD, *Classes of Welding Inspection*

SSTD-8070-0014-WELD, *Qualifying Welders and Welding Procedures*

## 4.0 RESPONSIBILITIES

Responsibilities for the use and control of this SSTD and for the review and approval of revisions or cancellation of this SSTD shall be as specified in SSTD-8070-0005-CONFIG and the applicable documents referenced therein.

## 5.0 REQUIREMENTS AND PROCEDURES

- a. All procedures shall be performed in compliance with applicable requirements in SPR 8715.1. If ever there is a conflict between this SSTD and the SPR, the SPR takes precedence.
- b. Items denoted as essential variables in the attached weld procedure specifications (WPS) shall not be altered when using the WPS. An alternate WPS may be used only if approved prior to use by the NASA SSC Center Operations Facilities Engineering Test Complex Support, the NASA SSC Engineering and Test Directorate, the NASA SSC Safety and Mission Assurance Office, and in accordance with ASME Boiler and Pressure Vessel Codes, Section IX, requirements.

Stennis Standard	SSTD-8070-0015-WELD	C
	<i>Number</i>	<i>Rev.</i>
	Effective Date:	January 11, 2021
	Review Date:	January 11, 2026
Page 5 of 11		
Responsible Office: NASA SSC Center Operations Facilities Engineering Test Complex Support		
<b>SUBJECT: GTAW Procedure for Carbon Steel (ASME P-No. 1, Group 1 or 2)</b>		

- c. The attached Procedure Qualification Record (PQR), NASA 300-1, is from the original WPS in this SSTD. When performing a new welder performance qualification (WPQ) or a new WPS, these documents shall be completed showing all pertinent data and results of the approved weld PQR.
- d. Welders shall be qualified in accordance with SSTD-8070-0014-WELD.
- e. Inspection methods for welds shall be in accordance with SSTD-8070-0013-WELD.
- f. Qualification tests shall be performed on test coupons welded with argon as the backing gases.

## 6.0 RECORDS AND FORMS

- a. Records required by the procedures of this SSTD shall be maintained in accordance with SPR 1440.1 and as specified in this SSTD.
- b. All records and forms are the latest version unless otherwise indicated.
- c. Forms may be obtained from the SSC Electronic Forms repository or from the NASA SSC Forms Management Officer. Quality Records are identified in the SSC Master Records Index.
- d. The original, signed WPS and PQR (copies of which are provided in Attachment A of this SSTD) and the accompanying Certificate(s) of Analysis validation test documents shall be maintained in Central Engineering Files (CEF).


## 7.0 ACRONYMS & ABBREVIATIONS

ASME	American Society of Mechanical Engineers
CEF	Central Engineering Files
GTAW	Gas Tungsten Arc Weld
"	Inch
NASA	National Aeronautics and Space Administration
PQR	Procedure Qualification Record
SPR	John C. Stennis Space Center Procedural Requirement
SSC	John C. Stennis Space Center
SSTD	John C. Stennis Space Center Standard
WPQ	Welder Procedure Qualification
WPS	Weld Procedure Specifications











Stennis Standard	SSTD-8070-0015-WELD	C
	Number	Rev.
	Effective Date:	January 11, 2021
	Review Date:	January 11, 2026
Page 6 of 11		
Responsible Office: NASA SSC Center Operations Facilities Engineering Test Complex Support		
<b>SUBJECT: GTAW Procedure for Carbon Steel (ASME P-No. 1, Group 1 or 2)</b>		

## 8.0 ATTACHMENTS


### 8.1 Welding Procedure Specification

 National Aeronautics and Space Administration John C. Stennis Space Center Stennis Space Center, MS 39529-6000		<b>ASME - WELDING PROCEDURE SPECIFICATIONS (WPS)</b>																																																							
Welding Procedure Specification Record Number SSTD-8070-0015-WELD		Date September 23, 2020	Revision Number 3																																																						
Qualified To ASME Boiler and Pressure Vessel Code		Company Name Syncom Space Services (S3)																																																							
Supporting PQR(s) SSTD-8070-0015-WELD (A)		Reference Docs. SSTD-8700-0015-WELD																																																							
Scope GTAW for Carbon Steel		Joint Single V Groove, Double V Groove																																																							
<b>BASE METALS</b> Type Carbon Steel P-no. P-1 Grp-no. 1or2 Welded To Carbon Steel P-no. P-1 Grp-no. 1or2 Backing Not Permitted P-no. Grp-no. Retainers Notes		<b>THICKNESS RANGE QUALIFIED</b> <table border="1"> <thead> <tr> <th>Min.</th> <th>As-welded Max.</th> <th>Min.</th> <th>With PWHT Max.</th> </tr> </thead> <tbody> <tr> <td>0.1875"</td> <td>1.50"</td> <td>N/A</td> <td>N/A</td> </tr> <tr> <td>Complete Pen.</td> <td></td> <td></td> <td></td> </tr> <tr> <td>Complete Pen.</td> <td></td> <td></td> <td></td> </tr> <tr> <td>Impact Tested</td> <td></td> <td></td> <td></td> </tr> <tr> <td>Impact Tested</td> <td></td> <td></td> <td></td> </tr> <tr> <td>Fillet Welds</td> <td></td> <td>N/A</td> <td>N/A</td> </tr> </tbody> </table>		Min.	As-welded Max.	Min.	With PWHT Max.	0.1875"	1.50"	N/A	N/A	Complete Pen.				Complete Pen.				Impact Tested				Impact Tested				Fillet Welds		N/A	N/A																										
Min.	As-welded Max.	Min.	With PWHT Max.																																																						
0.1875"	1.50"	N/A	N/A																																																						
Complete Pen.																																																									
Complete Pen.																																																									
Impact Tested																																																									
Impact Tested																																																									
Fillet Welds		N/A	N/A																																																						
<b>FILLER METALS</b> Process SFA Classification F-no. A-no. Chemical Analysis or Trade Name GTAW 5.18 ER70S-2 6 1 Cons. Insert N/A Flux N/A		<b>DIAMETER RANGE QUALIFIED</b> <table border="1"> <thead> <tr> <th>Min.</th> <th>As-welded Max.</th> <th>Min.</th> <th>With PWHT Max.</th> </tr> </thead> <tbody> <tr> <td>0.1875"</td> <td>1.50"</td> <td>N/A</td> <td>N/A</td> </tr> <tr> <td>Nominal Pipe Size</td> <td></td> <td>N/A</td> <td>N/A</td> </tr> </tbody> </table>		Min.	As-welded Max.	Min.	With PWHT Max.	0.1875"	1.50"	N/A	N/A	Nominal Pipe Size		N/A	N/A																																										
Min.	As-welded Max.	Min.	With PWHT Max.																																																						
0.1875"	1.50"	N/A	N/A																																																						
Nominal Pipe Size		N/A	N/A																																																						
<b>THICKNESS RANGE QUALIFIED</b> <table border="1"> <thead> <tr> <th>Min.</th> <th>As-welded Max.</th> <th>Min.</th> <th>With PWHT Max.</th> </tr> </thead> <tbody> <tr> <td>0.1875"</td> <td>1.50"</td> <td>N/A</td> <td>N/A</td> </tr> </tbody> </table>				Min.	As-welded Max.	Min.	With PWHT Max.	0.1875"	1.50"	N/A	N/A																																														
Min.	As-welded Max.	Min.	With PWHT Max.																																																						
0.1875"	1.50"	N/A	N/A																																																						
<b>WELDING PROCEDURE</b> <table border="1"> <tr> <td>Welding Process</td> <td>GTAW</td> </tr> <tr> <td>Type</td> <td>Manual</td> </tr> <tr> <td>Minimum preheat/interpass temperature (°F)</td> <td>50°F Min. (See Note A.)</td> </tr> <tr> <td>Maximum interpass temperature (°F)</td> <td>300°F Max.</td> </tr> <tr> <td>Tungsten Size</td> <td>1/16" - 1/8"</td> </tr> <tr> <td>Tungsten Type</td> <td>2% Thoriated (See Note B.)</td> </tr> <tr> <td>Filler Metal Size (in.)</td> <td>1/16" - 5/32"</td> </tr> <tr> <td>Layer Number</td> <td>1 - Cap</td> </tr> <tr> <td>Position of Groove</td> <td>ALL</td> </tr> <tr> <td>Weld Progression</td> <td>N/A</td> </tr> <tr> <td>Current/Polarity</td> <td>DCEN</td> </tr> <tr> <td>Amperes</td> <td>100 - 220</td> </tr> <tr> <td>Volts</td> <td>8 - 25</td> </tr> <tr> <td>Travel Speed (in./min)</td> <td>2 - 8 ipm</td> </tr> <tr> <td>Maximum Heat Input (kJ/in)</td> <td></td> </tr> <tr> <td>DC Pulsing Current</td> <td></td> </tr> <tr> <td>Shielding: Gas Type</td> <td>Argon ≥ 99.9% (See Note C.)</td> </tr> <tr> <td>Flow Rate (cfh)</td> <td>10 - 60 CFH</td> </tr> <tr> <td>Trailing: Gas Type</td> <td>N/A</td> </tr> <tr> <td>Flow Rate (cfh)</td> <td>N/A</td> </tr> <tr> <td>Backing: Gas Type</td> <td>Argon ≥ 99.9% (See Note D.)</td> </tr> <tr> <td>Flow Rate (cfh)</td> <td>10 - 60 CFH</td> </tr> <tr> <td>String or Weave</td> <td>String or Weave</td> </tr> <tr> <td>Orifice/Gas Cup Size</td> <td>1/4" - 3/4"</td> </tr> <tr> <td>Multi/Single Pass per Side</td> <td>Multiple</td> </tr> <tr> <td>Weld Deposit Chemistry</td> <td></td> </tr> <tr> <td>Notes</td> <td>See Notes E.</td> </tr> </table>				Welding Process	GTAW	Type	Manual	Minimum preheat/interpass temperature (°F)	50°F Min. (See Note A.)	Maximum interpass temperature (°F)	300°F Max.	Tungsten Size	1/16" - 1/8"	Tungsten Type	2% Thoriated (See Note B.)	Filler Metal Size (in.)	1/16" - 5/32"	Layer Number	1 - Cap	Position of Groove	ALL	Weld Progression	N/A	Current/Polarity	DCEN	Amperes	100 - 220	Volts	8 - 25	Travel Speed (in./min)	2 - 8 ipm	Maximum Heat Input (kJ/in)		DC Pulsing Current		Shielding: Gas Type	Argon ≥ 99.9% (See Note C.)	Flow Rate (cfh)	10 - 60 CFH	Trailing: Gas Type	N/A	Flow Rate (cfh)	N/A	Backing: Gas Type	Argon ≥ 99.9% (See Note D.)	Flow Rate (cfh)	10 - 60 CFH	String or Weave	String or Weave	Orifice/Gas Cup Size	1/4" - 3/4"	Multi/Single Pass per Side	Multiple	Weld Deposit Chemistry		Notes	See Notes E.
Welding Process	GTAW																																																								
Type	Manual																																																								
Minimum preheat/interpass temperature (°F)	50°F Min. (See Note A.)																																																								
Maximum interpass temperature (°F)	300°F Max.																																																								
Tungsten Size	1/16" - 1/8"																																																								
Tungsten Type	2% Thoriated (See Note B.)																																																								
Filler Metal Size (in.)	1/16" - 5/32"																																																								
Layer Number	1 - Cap																																																								
Position of Groove	ALL																																																								
Weld Progression	N/A																																																								
Current/Polarity	DCEN																																																								
Amperes	100 - 220																																																								
Volts	8 - 25																																																								
Travel Speed (in./min)	2 - 8 ipm																																																								
Maximum Heat Input (kJ/in)																																																									
DC Pulsing Current																																																									
Shielding: Gas Type	Argon ≥ 99.9% (See Note C.)																																																								
Flow Rate (cfh)	10 - 60 CFH																																																								
Trailing: Gas Type	N/A																																																								
Flow Rate (cfh)	N/A																																																								
Backing: Gas Type	Argon ≥ 99.9% (See Note D.)																																																								
Flow Rate (cfh)	10 - 60 CFH																																																								
String or Weave	String or Weave																																																								
Orifice/Gas Cup Size	1/4" - 3/4"																																																								
Multi/Single Pass per Side	Multiple																																																								
Weld Deposit Chemistry																																																									
Notes	See Notes E.																																																								

Stennis Standard	SSTD-8070-0015-WELD	C
	Number	Rev.
	Effective Date:	January 11, 2021
	Review Date:	January 11, 2026
Page 7 of 11		
Responsible Office: NASA SSC Center Operations Facilities Engineering Test Complex Support		
<b>SUBJECT: GTAW Procedure for Carbon Steel (ASME P-No. 1, Group 1 or 2)</b>		

 National Aeronautics and Space Administration John C. Stennis Space Center Stennis Space Center, MS 39529-6000	<b>ASME - WELDING PROCEDURE SPECIFICATIONS (WPS)</b>																	
	Welding Procedure Specification Record Number SSTD-8070-0015-WELD	Date September 23, 2020	Revision Number 3															
Qualified To ASME Boiler and Pressure Vessel Code	Company Name Syncom Space Services (S3)																	
<b>BASE METALS</b> Peening <u>Not allowed.</u> Surface Preparation <u>See Notes F.</u> Initial/Interpass Cleaning <u>Brushing or grinding</u> Back Gouging Method <u>N/A</u>																		
<b>POSTWELD HEAT TREATMENT</b> Temperature <u>None</u> Time and Temperature <u>None</u> Other <u>None</u>																		
<b>NOTES</b> A. Preheat maintenance as needed. B. Tungsten should maintain to a pencil point. C. High flow of shielding gas flow over molten puddle is required to eliminate nitrogen absorption from atmosphere. D. Minimum 10 minutes of back purge prior to welding. E. Contact Tube to Work Distance: 3/4" max F. Remove all contamination and water from surface. Clean weld and adjacent base metal using steel brushes or grinding.																		
<div style="display: flex; justify-content: space-between;"> <div> <b>Signature 1</b>  <table border="1"> <tr> <td>Engineer Name George Smith</td> <td>Signature </td> </tr> <tr> <td>Date 09/23/2020</td> <td></td> </tr> </table> </div> <div> <b>Signature 2</b>  <table border="1"> <tr> <td>Quality Name Richard Ladner</td> <td>Signature </td> </tr> <tr> <td>Date 09/23/2020</td> <td></td> </tr> </table> </div> </div> <div style="display: flex; justify-content: space-between; margin-top: 10px;"> <div> <b>Signature 3</b>  <table border="1"> <tr> <td>Customer Reviewer Name Benjamin McGrath</td> <td>Signature </td> </tr> <tr> <td>Date 09/23/2020</td> <td></td> </tr> </table> </div> <div> <b>Signature 4</b>  <table border="1"> <tr> <td>Customer Name</td> <td>Signature</td> </tr> <tr> <td>Date</td> <td></td> </tr> </table> </div> </div>			Engineer Name George Smith	Signature 	Date 09/23/2020		Quality Name Richard Ladner	Signature 	Date 09/23/2020		Customer Reviewer Name Benjamin McGrath	Signature 	Date 09/23/2020		Customer Name	Signature	Date	
Engineer Name George Smith	Signature 																	
Date 09/23/2020																		
Quality Name Richard Ladner	Signature 																	
Date 09/23/2020																		
Customer Reviewer Name Benjamin McGrath	Signature 																	
Date 09/23/2020																		
Customer Name	Signature																	
Date																		
SSC-937 (05/2019)		Page 2 of 3																










Stennis Standard	SSTD-8070-0015-WELD	C
	Number	Rev.
	Effective Date:	January 11, 2021
	Review Date:	January 11, 2026
Page 8 of 11		
Responsible Office: NASA SSC Center Operations Facilities Engineering Test Complex Support		
<b>SUBJECT: GTAW Procedure for Carbon Steel (ASME P-No. 1, Group 1 or 2)</b>		

 National Aeronautics and Space Administration John C. Stennis Space Center Stennis Space Center, MS 39529-6000		<b>ASME - WELDING PROCEDURE SPECIFICATIONS (WPS)</b>	
Welding Procedure Specification Record Number SSTD-8070-0015-WELD		Date September 23, 2020	Revision Number 3
Qualified To ASME Boiler and Pressure Vessel Code		Company Name Syncom Space Services (S3)	

**Weld Joint Designs**

**Attachment #1**

<b>Single-V Groove</b>  Groove Angle: 50 to 75 deg Root Opening: 1/16 to 3/16 in. Root Face: 0 to 1/16 in. Misalignment: 1/16-in. max.	<b>Single-Bevel Groove</b>  Groove Angle: 37.5 to 45 deg Root Opening: 1/16 to 3/16 in. Root Face: 0 to 1/16 in. Misalignment: 1/16-in. max.	<b>Double-V Groove</b>  Groove Angle: 50 to 75 deg Root Opening: 1/16 to 3/16 in. Root Face: 0 to 1/16 in. Misalignment: 1/16-in. max.
<b>Double-Bevel Groove</b>  Groove Angle: 37.5 to 45 deg Root Opening: 1/16 to 3/16 in. Root Face: 0 to 1/16 in. Misalignment: 1/16-in. max.	<b>Single-J Groove</b>  Groove Angle: 37.5 to 45 deg Groove Radius: 3/8 in. Root Opening: 1/16 to 3/16 in. Root Face: 0 to 1/16 in. Misalignment: 1/16-in. max.	<b>Double-J Groove</b>  Groove Angle: 37.5 to 45 deg Groove Radius: 3/8 in. Root Opening: 1/16 to 3/16 in. Root Face: 0 to 1/16 in. Misalignment: 1/16-in. max.
<b>Single-U Groove</b>  Groove Angle: 50 to 75 deg Groove Radius: 3/8 in. Root Opening: 1/16 to 3/16 in. Root Face: 0 to 1/16 in. Misalignment: 1/16-in. max.	<b>Double-U Groove</b>  Groove Angle: 50 to 75 deg Groove Radius: 3/8 in. Root Opening: 1/16 to 3/16 in. Root Face: 0 to 1/16 in. Misalignment: 1/16-in. max.	<b>Fillet Weld T or Lap</b>  Gap: 1/16-in. max. / Lap: 5 x t or 1 in. min.

Stennis Standard	SSTD-8070-0015-WELD	C
	Number	Rev.
	Effective Date:	January 11, 2021
	Review Date:	January 11, 2026
Page 9 of 11		
Responsible Office: NASA SSC Center Operations Facilities Engineering Test Complex Support		
SUBJECT: GTAW Procedure for Carbon Steel (ASME P-No. 1, Group 1 or 2)		

## 8.2 Welding Procedure Qualification Record

Accepted by Syncom Space Services LLC  
 George E. Smith 8/14/2017  
 Stephen A. Koch 8/14/2017



PROCEDURE QUALIFICATION RECORD (PQR)  
 (See QW-200.2, Section IX, ASME Boiler and Pressure Vessel Code)  
 Record Actual Conditions Used to Weld Test Coupon.

Company Name <u>Jacobs Technology</u>																	
Procedure Qualification Record No. <u>SSTD-8070-0015-WELD(A)</u>	Date <u>10/11/11</u>																
WPS No. <u>SSTD-8070-0015-WELD</u>																	
Welding Process(es) <u>GTAW</u>																	
Types (Manual, Automatic, Semi-Auto.) <u>Manual</u>																	
JOINTS (QW-402)																	
Groove Design of Test Coupon (For combination qualifications, the deposited weld metal thickness shall be recorded for each filler metal or process used.)																	
BASE METALS (QW-403) Material Spec. <u>ASTM A-36</u> Type or Grade <u>A-36</u> P-No. <u>1</u> to P-No. <u>1</u> Thickness of Test Coupon <u>0.750"</u> Diameter of Test Coupon <u>N/A</u> Other _____	POSTWELD HEAT TREATMENT (QW-407) Temperature <u>N/A</u> Time <u>N/A</u> Other _____																
FILLER METALS (QW-404) SFA Specification <u>5.18</u> AWS Classification <u>ER70S-2</u> Filler Metal F-No. <u>6</u> Weld Metal Analysis A-No. <u>1</u> Size of Filler Metal <u>3/32" - 1/8"</u> Other _____ Deposited Weld Metal <u>0.750"</u>	GAS (QW-408) <table border="1"> <thead> <tr> <th></th> <th>Gas(es)</th> <th>Percent Composition (Mixture)</th> <th>Flow Rate</th> </tr> </thead> <tbody> <tr> <td>Shielding</td> <td>Argon</td> <td>99.9</td> <td>20-60 CFH</td> </tr> <tr> <td>Trailing</td> <td>N/A</td> <td>N/A</td> <td>N/A</td> </tr> <tr> <td>Backing</td> <td>Argon</td> <td>99.9</td> <td>20-60 CFH</td> </tr> </tbody> </table>		Gas(es)	Percent Composition (Mixture)	Flow Rate	Shielding	Argon	99.9	20-60 CFH	Trailing	N/A	N/A	N/A	Backing	Argon	99.9	20-60 CFH
	Gas(es)	Percent Composition (Mixture)	Flow Rate														
Shielding	Argon	99.9	20-60 CFH														
Trailing	N/A	N/A	N/A														
Backing	Argon	99.9	20-60 CFH														
POSITION (QW-405) Position of Groove <u>1G</u> Weld Progression (Uphill, Downhill) <u>N/A</u> Other _____	ELECTRICAL CHARACTERISTICS (QW-409) Current <u>DC</u> Polarity <u>EN</u> Amps. <u>140 - 204</u> Volts <u>15.1 - 20.2</u> Tungsten Electrode Size <u>1/8"</u> Other _____																
PREHEAT (QW-406) Preheat Temp. <u>50°F Min.</u> Interpass Temp. <u>176°F - 273°F</u> Other _____	TECHNIQUE (QW-410) Travel Speed <u>3-5 IPM</u> String or Weave Bead <u>String &amp; Weave</u> Oscillation <u>N/A</u> Multipass or Single Pass (per side) <u>Multipass</u> Single or Multiple Electrodes <u>Single</u> Other _____																

*Frank J. Wood*

*By M. Sub  
10-14-11*

Stennis Standard	SSTD-8070-0015-WELD C
	Number _____ Rev. _____
	Effective Date: January 11, 2021
	Review Date: January 11, 2026
Page 10 of 11	
Responsible Office: NASA SSC Center Operations Facilities Engineering Test Complex Support	
<b>SUBJECT: GTAW Procedure for Carbon Steel (ASME P-No. 1, Group 1 or 2)</b>	

QW-483 (Back)

PQR No. SSTD-8070-0015-WELD(A)

Tensile Test (QW-150)

Specimen No.	Width	Thickness	Area	Ultimate Total Load lb	Ultimate Unit Stress psi	Type of Failure & Location
6438.90-T1	0.747"	0.725"	0.5416"	43,596	80,495	Base
6438.90-T2	0.754"	0.724"	0.5459"	43,090	78,934	Base

Guided-Bend Tests (QW-160)

Type and Figure No.	Result
6438.90-S1 Side Bend QW-462.2	Acceptable
6438.90-S2 Side Bend QW-462.2	Acceptable
6438.90-S3 Side Bend QW-462.2	Acceptable
6438.90-S4 Side Bend QW-462.2	Acceptable

Toughness Tests (QW-170)

Specimen No.	Notch Location	Notch Type	Test Temp.	Impact Values	Lateral Exp.		Drop Weight	
					% Shear	Mils	Break	No Break
N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A

Fillet-Weld Test (QW-180)

Result - Satisfactory: Yes N/A No N/A Penetration into Parent Metal: Yes N/A No N/A  
 Macro - Results N/A

Other Tests

Type of Test N/A  
 Deposit Analysis N/A  
 Other N/A

Welder's Name Scott Harriel & WC King Soc. Sec. No. \_\_\_\_\_ Stamp No. \_\_\_\_\_  
 Tests conducted by: Inspection Specialists, Inc. - MTL Div. Laboratory Test No. 6438.90  
 We certify that the statements in this record are correct and that the test welds were prepared, welded, and tested in accordance with the requirements of Section IX of the ASME Code.

Manufacturer Jacobs Technology

Date October 11, 2011 By Benny M. Salt 10-1415

Accepted by Syncom Space Services LLC

smith 8/14/2017




8/14/2017



Travis G I  
 CWI 990  
 QC1 EXP. 4/1/2014

Stennis Standard	SSTD-8070-0015-WELD	C
	Number	Rev.
	Effective Date:	January 11, 2021
	Review Date:	January 11, 2026
Page 11 of 11		
Responsible Office: NASA SSC Center Operations Facilities Engineering Test Complex Support		
<b>SUBJECT: GTAW Procedure for Carbon Steel (ASME P-No. 1, Group 1 or 2)</b>		

### 8.3 Certificate of Analysis

 <p>INSPECTION SPECIALISTS, INC. MECHANICAL TESTING LABORATORY DIVISION</p>						
<b>CERTIFICATE OF ANALYSIS</b>						
Client: <u>Jacobs Technology</u>				Job No: <u>6438.90</u>		
Client Representative: <u>Benny McGrath</u>				Purchase Order: _____		
Test Specification: <u>ASME Section IX</u>						
Sample Identification: <u>One (1) – 0.750" Plate Procedure Qualification WPS # SSTD-8070-0015-WELD</u> Welders: <u>Scott Harriel &amp; WC King</u>						
<p>The above referenced sample was prepared and tested in accordance with the welding procedure qualification requirements of ASME Section IX. Two (2) tensile test specimens and four (4) guided bend test specimens were prepared and tested. The results of these tests are reported herein.</p>						
<b>TENSILE TEST</b>						
SPECIMEN ID	WIDTH INCHES	THICKNESS INCHES	AREA SQ. IN.	ULTIMATE LOAD POUNDS	TENSILE STRENGTH PSI	NATURE OF FRACTURE
6438.90 –T1	0.747"	0.725"	0.5416"	43,596	80,495	Base
6438.90 –T2	0.754"	0.724"	0.5459"	43,090	78,934	Base
<b>GUIDED BEND TEST</b>						
SPECIMEN ID	TYPE TEST		TEST RESULT			
6438.90 –S1	Side Bend		Acceptable			
6438.90 –S2	Side Bend		Acceptable			
6438.90 –S3	Side Bend		Acceptable			
6438.90 –S4	Side Bend		Acceptable			
<p>The tests expressed herein meet or exceed the requirements of ASME Section IX.</p>						
<div style="display: flex; justify-content: space-between; align-items: flex-end;"> <div>  <p>Travis G Moore CWI 99041251 QC1 EXP. 4/1/2014</p> </div> <div style="text-align: right;"> <p><i>Benny McGrath 10-14-11</i></p> </div> </div>						
<p><b>CERTIFIED BY:</b></p> <p> Date: <u>October 11, 2011</u> Certificate No: <u>1</u> of <u>1</u></p> <p>Travis G. Moore, Lab Manager</p>						
ALL TEST SPECIMENS, SAMPLES, DROPS, ETC. WILL BE DISCARDED THIRTY (30) DAYS AFTER TESTING UNLESS OTHERWISE INSTRUCTED IN WRITING.						